

EchoPanel Vee Tiles Installation Guide

Note: Please read the entire Installation Guide before application.

The installation guide is intended to provide installers with helpful information regarding EchoPanel® Vee Tiles prior to installing the material. Kirei accepts no responsibility for installation actions taken or not taken. This installation guide is not intended to be an in-depth guide; installers' knowledge as experienced tradesman needs to be applied.

This installation guide serves only as a recommendation for installing and handling EchoPanel Vee Tiles. If you have questions about application or techniques, contact Kirei at www.kireiusa.com or 619.236.9924.

ECHOPANEL VEE TILES SPECIFICATIONS

What are EchoPanel Vee Tiles?

Vee Tiles are a decorative surface finish offering acoustic performance with a felt-like finish. EchoPanel is a decorative acoustically absorbent material with a felt-like finish. It is made from 100% PET thermally stable plastic which, depending on the color, contains up to 60% post-consumer content. EchoPanel is also recyclable in the PET waste stream. Please consult the Vee Tiles spec sheet for material specifications.

Fire Rating

EchoPanel Vee Tiles are rated ASTM E84 Class C. Vee Tiles can be treated to satisfy Class A requirements as needed. Check the Fire Rating requirements for your Project, Building or Municipality in advance. ASTM E84 test results can be obtained by contacting Kirei.

Low VOC Material

EchoPanel is considered a low-VOC emitting material making it a healthy building option for interior finishes. EchoPanel is CDPH (CA 01350) Compliant TVOC: <0.5 mg/m³, and Ecospecifier GreenTag Compliant; TVOC: 0.015 MG/M²/HR (ASTM D5516).

Handling and Storage

Keep it clean! EchoPanel is an absorbent material and traps dirt, grime and debris just as well as it does sound. White glove handling is recommended for prep, processing and installation. Kirei is not responsible for mishandling on the job site.

Keep it flat! If cutting, drilling or mounting hardware on site, make sure that Vee Tiles are evenly supported on a flat, clean surface. Improperly handled material can crease.

Storage areas should be clean, dry, cool, and well ventilated.

EchoPanel Vee Tiles Installation Guide

Handling and Storage (Cont.)

All Vee Tiles products are inspected prior to shipment. Kirei is not responsible for damage in shipment or in storage; customers should carefully inspect all items at time of delivery and note any obvious damage on the delivery receipt. For the customer's protection subsequently discovered concealed damage must be reported immediately to the carrier. Claims to Kirei will not be considered if the sheet has been worked by the customer or others. No claims for labor charges will be allowed in any circumstances.

To handle and store Vee Tiles properly, follow these guidelines:

- Carefully inspect all material at time of delivery and note any obvious damage on the delivery receipt.
- Store Vee Tiles horizontally with support.
- Keep Vee Tiles as clean as possible during storage. Vee Tiles should be kept free from grease, wax, dust, and chips that could leave impression.
- Store Vee Tiles indoors, in a dry, cool, well-ventilated area.
- Avoid exposure to heat 150°F (65°C) or greater.
- Keep table tops clean to avoid scratching.
- Inspect for defects, then recover for protection during fabrication.
- Wear clean white gloves when handling Vee Tiles.
- Do NOT store Vee Tiles near radiators, steam pipes, or in direct sunlight.

Cleaning and Care

Remove dust and dirt by dusting, vacuuming, or with a soft cloth or sponge and a solution of carpet or upholstery shampoo. Always use a soft, damp cloth and blot dry. Spot cleaner such as ZEP Commercial Instant Spot Remover has been used with success for some light soil situations. No guarantee is given for cleaning results with this product.

EchoPanel Vee Tiles Installation Guide

Installation

Preparation

Carefully plan your installation to ensure you have sufficient number of tiles for the project by laying up the tiles on the floor first. Plan, measure and mark your layout in advance to ensure accuracy of placement. Vee Tiles adhesive is very strong and is not designed for repositioning or adjusting.

Mounting

Prior to installation, ensure the surface area to which the tiles are going to be fixed is smooth, clean and free from dust or any other contaminant that may impede the installation. We recommend a test panel be used on the substrate to determine that the adhesive is suitable for the application.

Vee Tiles should be installed with standard construction adhesive (no PVA glue). Apply adhesive to the back of the tile in a regular pattern, leaving room at the edges for glue to spread.

After applying adhesive, mount Vee Tiles per layout and maintain even pressure per adhesive manufacturer instructions. Clean any excess adhesive.

Work Safety

In the interest of work safety, it is recommended that people working with Kirei Vee Tiles wear the appropriate safety equipment. Although the product emits zero off-gases, masks and gloves should be worn to ensure the maximum possible safety precautions. For an SDS form, please contact Kirei at info@kireiusa.com or 619-236-9924.

Final Note

Kirei will not be responsible for any cutting or mounting not performed by Kirei staff.

For any other questions or concerns, please contact Kirei.