

EchoPanel Geometry Tile Installation Guide

The installation guide is intended to provide installers with helpful information regarding EchoPanel Geometry Tile prior to installing the material. Kirei accepts no responsibility for installation actions taken or not taken. This Installation Guide is not intended to be an in-depth guide; installers' knowledge as experienced tradesman needs to be applied.

ECHOPANEL GEOMETRY TILE SPECIFICATIONS

What are EchoPanel Geometry Tiles?

Geometry Tiles are a decorative surface finish offering acoustic performance with a felt-like finish. They are produced from 100% PET (Polyethylene Terephthalate) which, depending on color, contains up to 60% post consumer content.

The current styles and dimensions per style can be found on the Geometry Tile spec sheet and on Kirei's website.

How are Geometry Tiles used?

Geometry tiles are used in many types of settings, including commercial, hospitality, restaurant, education, residential and entertainment spaces

HANDLING & STORAGE

Geometry Tiles should be stored flat. Storage areas should be clean, dry, cool, and well ventilated.

CLEANING & CARE

Remove dust and dirt by dusting, vacuuming, or with a soft cloth or sponge and a solution of carpet or upholstery shampoo. Always use a soft, damp cloth and blot dry. Spot cleaner such as ZEP Commercial Instant Spot Remover has been used with success for some light soil situations. No guarantee is given for cleaning results with this product.

GEOMETRY TILE INSTALLATION NOTES

Surface Preparation

Ensure the surface area is clean and free from dust or any other contaminant that may impede the installation.

Geometry Tile Preparation

Carefully plan your installation to ensure you have sufficient number of tiles for the project by laying up the tiles on the floor first.

EchoPanel Geometry Tile Installation Guide

Plan, measure and mark your layout in advance to ensure accuracy of placement. Geometry Tile adhesive is very strong and is not designed for repositioning or adjusting.

Mounting

Prior to installation, ensure the surface area to which the tiles are going to be fixed is smooth, clean and free from dust or any other contaminant that may impede the installation. We recommend a test panel be used on the substrate to determine that the adhesive is suitable for the application.

Geometry Tiles have an adhesive backing. Peel off the backing and stick on to substrate. Pressure should be used when applying to any substrate.

FINAL NOTE

Kirei will not be responsible for any cutting or mounting not performed by Kirei staff.

WORK SAFETY

In the interest of work safety, it is recommended that people working with Kirei EchoPanel® wear the appropriate safety equipment. Although the product emits zero off-gases, masks and gloves should be worn to ensure the maximum possible safety precautions. For an MSDS form, please contact Kirei.