



EchoPanel | Color Options



EchoPanel | Color 442 (Grey)

Style	Metric	Standard	Thickness	Weight	SF/Panel
12mm Panel	1200mm x 2800mm	47.24 in. x 110.24 in.	12mm	18 lbs	36.2
24mm Panel	1200mm x 2800mm	47.24 in. x 110.24 in.	24mm	22 lbs	36.2

All specs refer to singular products and not multiples unless specified. Due to the nature of the material, cutting and fabrication process, minor dimensional variances may occur. Custom options available upon request. EchoPanel is sold individually and ships flat. Please note that not all colors come in all thicknesses. Refer to the sample board for color and size availability.

EchoPanel

EchoPanel®, a registered trademark of Woven Image®, is a decorative, acoustically-absorbent panel with a felt-like finish that is made from 100% PET plastic, with at least 60% recycled content. EchoPanel is a low-VOC material, meeting requirements for LEED and other green building certifications. A Declared, Red-List Free material, EchoPanel qualifies for the Living Building Challenge.

Individual panels can be installed on walls and ceilings as well as in a variety of office furniture systems, wall panel systems and ceiling grid systems. Kirei’s collection of expertly-crafted EchoPanel acoustic design elements imagines the possibilities of a single panel, allowing designers to create truly memorable spacial experiences without the heavy-lifting. From decorative wall tiles to ceiling clouds and baffles, EchoPanel’s strength shows through it’s material simplicity and design versatility.

Installation

EchoPanel can be installed on walls and ceilings as well as in office furniture systems and wall panel systems. Panels can be customized into clouds, baffles, tiles, and more. EchoPanel is also tackable for a multipurpose solution in office spaces or educational facilities. For instructions on how to install panels in a variety of ways, please visit our website and download our EchoPanel Installation Guide.

Customization

EchoPanel can be digitally printed and custom cut with CNC, laser, water-jet or hand knife to make your design ideas come to life. For information on custom printing and cutting of EchoPanel, please contact Kirei.

Fire Rating

12mm & 24mm Panels: ASTM E84 Class A

VOC Emissions

CDPH (CA 01350) Compliant; TVOC: <0.5 mg/m3

Ecospecifier GreenTag Compliant; TVOC: 0.015 mg/m2/hr (ASTM D5116)

Available Colors and Material Thickness



Sabins per 12mm EchoPanel

Frequency	250Hz	500Hz	800Hz	1000Hz	2000Hz	4000Hz	NRC
m ² /Object	0.70	2.20	4.30	5.74	8.66	10.57	0.45 (no air gap)
m ² /Object (20mm air gap)	1.51	4.33	7.35	8.56	9.97	9.97	0.60 (20mm air gap)
m ² /Object (50mm air gap)	3.32	7.35	9.87	10.07	9.67	10.07	0.75 (50mm air gap)
m ² /Object (1" fiberglass)	4.33	6.78	6.66	6.58	6.47	7.10	0.90 (1" fiberglass)
m ² /Object (2" fiberglass)	6.56	7.35	7.03	6.49	6.60	6.80	1.00 (2" fiberglass)

Sabins per 24mm EchoPanel

Frequency	250Hz	500Hz	800Hz	1000Hz	2000Hz	4000Hz	NRC
m ² /Object	1.85	6.65	9.36	10.72	11.83	11.83	0.65 (no air gap)
m ² /Object (20mm air gap)	2.59	8.13	11.33	12.57	12.57	12.20	0.75 (20mm air gap)
m ² /Object (50mm air gap)	4.93	10.96	13.18	13.06	11.70	11.95	0.85 (50mm air gap)
m ² /Object (2" fiberglass)	6.97	7.77	7.35	6.97	6.88	7.01	1.05 (2" fiberglass)